

SUN ECO PLUS ALTA

Technical specifications:

- Stainless steel construction
- Custom backlit LCD display
- High-speed washable touchless keyboard
- 8 dots/mm thermal printer with "easy loading" device
- Linerless adhesive paper option
- Print speed 70 mm/s
- Paper width 57mm
- Programmable receipt header (5 lines of 26 characters)
- Automatic date and time management
- Single or cumulative receipt
- Print date and expiry date
- Print list of ingredients associated with the PLU (6 lines of 45 micro characters)
- Batch insertion and printing
- EAN13 barcode printing
- 999 programmable PLUs - Quick price change
- Change function
- Re-opening receipt function
- Reverse entry function
- Semi-automatic, manual, pre-stored and associated tare
- Partial total of 4 operators on screen
- Up to 6 scales in LAN network (wired or RF)
- Scale programming from PC
- General, PLU and operator totals
- Optional radio frequency kit
- 4-8-16 operators
- External 12/24V power supply
- Internal battery autonomy of about 35/40 hours
- Customer-side advertising
- Available capacities: 30kg/5g; 12-30kg/2-5g; 12kg/2g; 6kg/1g



Model	Code
SUN ECO PLUS ALTA KG.12/30 MULTIRANGE 4/8/16 operators	NSUS030-N8

Accessoires et options	Code
Basin plate	OSU0PTB
Networking cable	ACVTEL-4X0.12
Factory fitted 12/24V output	ASE9001.0.AMBUL
Factory-fitted radio frequency kit	OSU0RFQ
Stainless steel foot each	APV10449IM10X25
Top quality adhesive paper printer kit factory fitted	AASKEDP
Thermal neutral roll 57x30 each	CRCT-57B
Adhesive linerless 55.5x18 each	CRAZ-57X50X18
Confbil configuration software	WCONF-ECO
Scale cover	ACOPRIBILANCIA
Ethernet card	ASE5076-ETH