

# SUN ECO PLUS BASSA



## Technical specifications:

- Stainless steel frame
- Custom backlit LCD display
- High-speed washable touchless keyboard
- 8 dots/mm thermal printer with "easy loading" feature
- Linerless adhesive paper option
- Print speed 70 mm/s
- Paper width 57mm
- Programmable receipt header (5 lines of 26 characters)
- Automatic date and time management
- Single or cumulative receipt
- Printing of packing date and expiry date
- Print list of ingredients associated with the PLU (6 lines of 45 micro characters)
- Batch insertion and printing
- EAN13 barcode printing
- Change Function
- Re-opening receipt function
- Reverse entry function
- Semi-automatic, manual, pre-stored and associated tare
- Partial total of 4 operators on screen
- Up to 6 scales in LAN network (wired or RF)
- Scale Programming from PC
- General, PLU and operator totals
- Optional radio frequency kit
- 4-8-16 operators
- Optional 12/24V external power supply
- Internal battery autonomy of about 35/40 hours
- Customer-side advertising
- Available capacities: 30kg/5g; 12-30kg/2-5g; 12kg/2g; 6kg/1g

## Model

SUN ECO PLUS BASSA KG.12/30 MULTIRANGE 4/8/16 operators

## Code

NSUS030-N8/B

## Accessories and options

| Accessories and options                | Code            |
|--|-----------------|
| Basin plate                            | OSU0PTB         |
| Networking cable                       | ACVTEL-4X0.12   |
| Factory fitted 12/24V output           | ASE9001.0.AMBUL |
| Factory-fitted radio frequency kit     | OSU0RFQ         |
| Stainless steel foot each              | APV10449IM10X25 |
| Top quality adhesive paper printer kit | AASKEDP         |
| Thermal neutral roll 57x30 each        | CRCT-57B        |
| Adhesive linerless 55.5x18 each        | CRAZ-57X50X18   |
| Confbil configuration software         | WCONF-ECO       |
| Ethernet card                          | ASE5076-ETH     |