

SUN ECO

Technical specifications:

- Stainless steel construction
- Custom LCD backlit display
- Mechanical keyboard with rubber keys
- 8 dots/mm thermal printer with "easy loading" device
- Linerless adhesive paper option
- 70mm/s print speed
- 57mm paper width
- Programmable receipt header (5 lines of 26 characters)
- Automatic date and time management
- Single or cumulative receipt
- Printing of packing date and expiry date
- Printing of ingredient list associated to the PLU (6 lines of 45micro characters)
- Batch insertion and printing
- EAN13 barcode printing
- 999 programmable PLUs
- Quick price change
- Change function
- Re-opening receipt function
- Reverse entry function
- Semi-automatic, manual, pre-stored and associated tare
- Partial total of 4 operators on screen
- Up to 6 scales in LAN network (wired or RF)
- Scale programming from PC
- General, PLU and operator totals
- Optional radio frequency kit
- 4-8-16 operators
- Optional 12/24V external power supply
- Internal battery with autonomy of about 35/40 hours
- Customer-side advertising
- Available capacities: 30kg/5g; 12-30kg/2-5g; 12kg/2g; 6kg/1g



Model	Code
SUN ECO KG.12/30 MULTIRANGE 4/8/16 operators	NSUE030-N8
Accessories and options	Code
Basin plate	OSU0PTB
Networking cable	ACVTEL-4X0.12
Factory fitted 12/24V output	ASE9001.0.AMBUL
Factory-fitted radio frequency kit	OSU0RFQ
Stainless steel foot each	APV10449IM10X25
Top quality adhesive paper printer kit factory fitted	AASKEDP
Transparent key cap	ACOPRITASTI
Thermal neutral roll 57x30 each	CRCT-57B
Adhesive linerless 55.5x18 each	CRAZ-57X50X18
Confbil configuration software	WCONF-ECO
Scale cover	ACOPRIBILANCIA
Ethernet card	ASE5076-ETH