

SUN ECO BASSA



Technical specifications:

- Stainless steel construction
- Custom LCD backlit display
- Mechanical keyboard with rubber keys
- 8 dots/mm thermal printer with "easy loading" device
- Linerless adhesive paper option
- 70mm/s print speed
- 57mm paper width
- Programmable receipt header (5 lines of 26 characters)
- Automatic date and time management
- Single or cumulative receipt
- Printing of packing date and expiry date
- Printing of ingredient list associated to the PLU (6 lines of 45micro characters)
- Batch insertion and printing
- EAN13 barcode printing
- 999 programmable PLUs
- Fast price change
- Change function
- Reopening receipt function
- Reverse entry function
- Semi-automatic, manual, pre-stored and associated tare
- Partial total of 4 operators on screen
- Up to 6 scales in LAN network (wired or RF)
- Scale Programming from PC
- General, PLU and operator totals
- Optional radio frequency kit
- 4-8-16 operators
- Optional 12/24V external power supply
- Internal battery with autonomy of about 35/40 hours
- Customer-side advertising
- Available capacities: 30kg/5g; 12-30kg/2-5g; 12kg/2g; 6kg/1g

Model

SUN ECO KG.12/30 MULTIRANGE 4/8/16 operators

Code

NSUB030-N8

Accessories and options

Basin plate

OSU0PTB

Networking cable

ACVTEL-4X0.12

Factory fitted 12/24V output

ASE9001.0.AMBUL

Factory-fitted radio frequency kit

OSU0RFQ

Stainless steel foot each

APV10449IM10X25

Top quality adhesive paper printer kit factory

AASKEDP

Transparent key cap

ACOPRITASTI

Thermal neutral roll 57x30 each

CRCT-57B

Adhesive linerless 55.5x18 each

CRAZ-57X50X18

Confbil configuration software

WCONF-ECO

Ethernet card

ASE5076-ETH



RETAIL